


GATE-2007

**Question Paper
&
Answer Keys**

Index

1. Question Paper Analysis
2. Question Paper & Answer keys

ANALYSIS OF GATE 2007 Civil Engineering



GATE-2007- CE

SUBJECT	NO OF QUESTION	Topics Asked in Paper	Total Marks
Engineering Mathematics	1 M: 3 2 M: 9	Linear Algebra, Differential Equations Calculus, Numerical Methods Complex Variables, Probability and Distribution	21
Solid Mechanics	1 M: 2 2 M: 5	Simple Stress & Strain, Torsion Stresses in Beams	12
Structural Analysis	1 M: 1 2 M: 4	Matrix Method of Structural Analysis Influence Line Diagram and Rolling Loads Slope and Deflection Method	9
Reinforced Cement Concrete	1 M: 0 2 M: 6	Concrete Technology Basic Elements of Pre-stressed Concrete Design of Pre-Stressed Concrete Beams Basic of Mix Design Analysis of Ultimate Load Capacity	12
Steel Structures	1 M:1 2 M:3	Columns and Struts, Design of Tension Member Simple Connections, Plastic Analysis	7
Geotechnical Engineering	1 M: 3 2 M: 10	Stress Analysis Surface Investigations Index Properties and Soil Classification Three Phase System, Fundamental Definitions and Relationship, Stability of Slopes Permeability and Seepage, Bearing Capacity Pile Foundation, Consolidation	23
Fluid Mechanics	1 M: 1 2 M: 3	Fluid Dynamics, Dimensional Analysis Boundary Layer	7
Hydrology & Irrigation	1 M: 3 2 M: 8	Open Channel Flow, Water Requirements of Crops, Sedimentation, Transport and Design of Irrigation Channels, Open Channel Flow Hydrology	19
Environmental Engineering	1 M: 3 2 M: 6	Quality Standards of Water Air Pollution and Noise Pollution Solid Waste Management Waste Water Treatment Water Supply and its Treatment	15
Transportation Engineering	1 M: 3 2 M: 7	Testing and Specifications of Paving Materials Traffic Characteristics, Traffic Signs and Signal Design, Geometric Design of Highway Design of Rigid Flexible Pavements, Intersection Design	17
Geomatics Engineering	1 M: 0 2 M: 4	Introduction to Geomatics Theodolite & Traversing, Leveling Measurement of Distance & Direction	8
Total	85		150

**GATE 2007 Examination
Civil Engineering**

Q.1 - Q.20 Carry One Mark each.

1. The minimum and the maximum eigen values of the matrix $\begin{matrix} 1 & 1 & 3 \\ 1 & 5 & 1 \\ 3 & 1 & 1 \end{matrix}$ are -2 and 6 , respectively. What is the other eigen value?
 (A) 5 (C) 1
 (B) 3 (D) -1
[Ans. B]
2. The degree of the differential $\frac{d^2x}{dt^2} + 2x^3 = 0$ is
 (A) 0 (C) 2
 (B) 1 (D) 3
[Ans. B]
3. The solution for the differential equation $\frac{dy}{dx} = x^2y$ with condition that $y = 1$ at $x = 0$ is
 (A) $y = e^{\frac{1}{2x}}$ (C) $\ln(y) = \frac{x^2}{2}$
 (B) $\ln(y) = \frac{x^3}{3} + 4$ (D) $y = e^{\frac{x^3}{3}}$
[Ans. D]
4. An axially loaded bar is subjected to a normal stress of 173 MPa. The shear stress in the bar is
 (A) 75MPa (C) 100MPa
 (B) 86.5MPa (D) 122.3MPa
[Ans. B]
5. A steel column pinned at both ends, has a buckling load of 200 kN. If the column is restrained against lateral movement at its mid-height, its buckling load will be
 (A) 200 kN (C) 400 kN
 (B) 283 kN (D) 800 kN
[Ans. D]
6. The stiffness coefficient k_{ij} indicates
 (A) Force at i due to a unit deformation at j (C) Deformation at i due to a unit force at j
 (B) Deformation at j due to a unit force at i (D) Force at j due to a unit deformation at i
[Ans. A]
7. For an isotropic material, the relationship between the Young's modulus (E), shear modulus (G) and Poisson's ratio (μ) is given by
 (A) $G = \frac{E}{2(1 + \mu)}$ (C) $G = \frac{E}{(1 + 2\mu)}$
 (B) $E = \frac{E}{2(1 + \mu)}$ (D) $G = \frac{E}{2(1 - 2\mu)}$
[Ans. A]

8. A clay soil sample is tested in a triaxial apparatus in consolidated drained conditions at a cell pressure of 100 kN/m^2 . What will be the pore water pressure at a deviator stress of 40 kN/m^2 ?
- (A) 0 (C) 40 kN/m^2
(B) 20 kN/m^2 (D) 60 kN/m^2

[Ans. A]

9. The no. of blows observed in a standard penetration test (SPT) for different penetration depths are given as follows:

Penetration of sampler	Number of blows
0 - 150 mm	6
150 - 300 mm	8
300 - 450 mm	10

The observed N value is

- (A) 8 (C) 18
(B) 14 (D) 24

[Ans. C]

10. The vertical stress at some depth below the corner of a $2 \text{ m} \times 3 \text{ m}$ rectangular footing due to a certain load intensity is 100 kN/m^2 . What will be the vertical stress in kN/m^2 below the centre of a $4 \text{ m} \times 6 \text{ m}$ rectangular footing at the same depth and same load intensity?
- (A) 25 (C) 200
(B) 100 (D) 400

[Ans. D]

11. There is a free overall at the end of a long open channel. For a given flow rate, the critical depth is less than normal depth. What gradually varied flow profile will occur in the channel for this flow rate?
- (A) M_1 (C) M_3
(B) M_2 (D) S_1

[Ans. B]

12. The consumptive use of water for a crop during a particular stage of growth is 2.0 mm/day . The maximum depth of available water in the root zone is 60 mm . Irrigation is required when the amount of available water is 50% of the maximum available water in the root zone. Frequency of irrigation should be
- (A) 10 days (C) 20 days
(B) 15 days (D) 25 days

[Ans. B]

13. As per the Lacey's method for design of alluvial channels, identify the TRUE statement from the following:
- (A) Wetted perimeter increases with an increase in design discharge
(B) Hydraulic radius increases with an increase in silt factor
(C) Wetted perimeter decreases with an increase in design discharge
(D) Wetted perimeter increases with an increase in silt factor

[Ans. A]

14. At two points 1 and 2 in a pipeline the velocities are V and $2V$, respectively. Both the points are at the same elevation. The fluid density is ρ . The flow can be assumed to be incompressible, inviscid, steady and irrotational. The difference in pressures P_1 and P_2 at points 1 and 2 is
(A) $0.5\rho V^2$ (C) $2\rho V^2$
(B) $1.5\rho V^2$ (D) $3\rho V^2$
[Ans. B]
15. The presence of hardness in excess of permissible limit causes
(A) Cardio - vascular problem
(B) Skin discoloration
(C) Calcium deficiency
(D) Increased laundry expenses
[Ans. D]
16. The dispersion of pollutants in atmosphere is maximum when
(A) Environment lapse rate is greater than adiabatic lapse rate
(B) Environment lapse rate is less than adiabatic lapse rate
(C) Environment lapse rate is equal to adiabatic lapse rate
(D) Maximum mixing depth is equal to zero
[Ans. A]
17. The alkalinity and the hardness of a water sample are 250 mg/L and 350 mg/L as CaCO_3 respectively. The water has
(A) 350 mg/L carbonate hardness and zero non-carbonate hardness
(B) 250mg/L carbonate hardness and zero non-carbonate hardness.
(C) 250mg/L carbonate hardness and 350 mg/L non-carbonate hardness
(D) 250 mg/L carbonate hardness and 100 mg/L non-carbonate hardness
[Ans. D]
18. The consistency and flow resistance of bitumen can be determined from the following.
(A) Ductility test (C) Softening point Test
(B) Penetration test (D) Viscosity Test
[Ans. D]
19. If a two-lane national highway and a two-lane state highway intersect at right angles, the number of potential conflict points at the intersection, assuming that both the roads are two-way is
(A) 11 (C) 24
(B) 17 (D) 32
[Ans. C]
20. In signal design as per Indian Roads Congress specification, if the sum of the ratios of normal flows to saturation flow of two directional traffic flow is 0.50 and the total lost time per cycle is 10 seconds, the optimum cycle length in seconds is
(A) 100 (C) 60
(B) 80 (D) 40
[Ans. D]

Q.21 to Q.75 carry two marks each

21. For what values of α and β the following simultaneous equations have an infinite number of solutions?

$$x + y + z = 5; \quad x + 3y + 3z = 9; \quad x + 2y + \alpha z = \beta$$

- (A) 2,7 (C) 9,3
(B) 3,8 (D) 7,2

[Ans. A]

22. A velocity vector is given as

$$\vec{v} = 5xy \vec{i} + 2y^2 \vec{j} + 3yz^2 \vec{k} \quad \text{The divergence of this velocity vector at (1,1,1) is}$$

- (A) 9 (C) 14
(B) 10 (D) 15

[Ans. D]

23. A body originally at 60°C cools down to 40°C in 15 minutes when kept in air at a temperature of 25°C . What will be the temperature of the body at the end of 30 minutes?

- (A) 35.2°C (C) 28.7°C
(B) 31.5°C (D) 15°C

[Ans. B]

24. The following equation needs to be numerically solved using the Newton-Raphson method.

$$x^3 + 4x - 9 = 0. \quad \text{The iterative equation for this purpose is (k indicates the iteration level)}$$

- (A) $x_{k+1} = \frac{2x_k^3 + 9}{3x_k^2 + 4}$ (C) $x_{k+1} = x_k - 3x_k^2 + 4$
(B) $x_{k+1} = \frac{3x_k^2 + 4}{2x_k^2 + 9}$ (D) $x_{k+1} = \frac{4x_k^2 + 3}{9x_k^2 + 2}$

[Ans. A]

25. Evaluate $\int_0^\infty \frac{\sin t}{t} dt$

- (A) π (C) $\frac{\pi}{4}$
(B) $\frac{\pi}{2}$ (D) $\frac{\pi}{3}$

[Ans. B]

26. Potential function ϕ is given as $\phi = x^2 + y^2$. What will be the stream function (ψ) with the condition $\psi = 0$ at $x = y = 0$?

- (A) $2xy$ (C) $x^2 - y^2$
(B) $x^2 + y^2$ (D) $2x^2y^2$

[Ans. A]


27. The inverse of the 2×2 matrix $\begin{bmatrix} 1 & 2 \\ 5 & 7 \end{bmatrix}$ is

- (A) $\frac{1}{3} \begin{bmatrix} -7 & 2 \\ 5 & -1 \end{bmatrix}$ (C) $\frac{1}{3} \begin{bmatrix} 7 & -2 \\ -5 & 1 \end{bmatrix}$
(B) $\frac{1}{3} \begin{bmatrix} 7 & 2 \\ 5 & 1 \end{bmatrix}$ (D) $\frac{1}{3} \begin{bmatrix} -7 & -2 \\ -5 & -1 \end{bmatrix}$

[Ans. *]


28. Given that one root of the equation $x^3 - 10x^2 + 31x - 30 = 0$ is 5, the other two roots are
 (A) 2 and 3 (C) 3 and 4
 (B) 2 and 4 (D) -2 and -3
[Ans. C]
29. If the standard deviation of the spot speed of vehicles in a highway is 8.8 kmph and the mean speed of the vehicles is 33kmph, the coefficient of variation in speed is
 (A) 0.1517 (C) 0.2666
 (B) 0.1867 (D) 0.3646
[Ans. A]
30. A metal bar of length 100 mm is inserted between two rigid supports and its temperature is increased by 10°C . If the coefficient of thermal expansion is 12×10^{-6} per $^\circ\text{C}$ and the Young's modulus is 2×10^5 MPa, the stress in the bar is
 (A) Zero (C) 24MPa
 (B) 12 MPa (D) 2400 MPa
[Ans. C]
31. A rigid bar is suspended by three rods made of the same material as shown in the figure. The area and length of the central rod are 3 A and L, respectively while that of the two outer rods are 2A and 2L, respectively. If a downward force of 50kN is applied to the rigid bar, the forces in the central and each of the outer rods will be
 (A) 16.67 kN each (C) 30 kN and 10 kN
 (B) 30 kN and 15 kN (D) 21.4 kN and 14.3 kN
[Ans. C]
32. The maximum and minimum shear stresses in a hollow circular shaft of outer diameter 20 mm and thickness 2 mm, subjected to a torque of 92.7 N-m will be
 (A) 59 MPa and 47.2 MPa (C) 118 MPa and 160 MPa
 (B) 100 MPa and 80 MPa (D) 200 MPa and 160 MPa
[Ans. B]
33. The shear stress at the neutral axis in a beam of triangular section with a base of 40 mm and height 20 mm, subjected to a shear force of 3 kN is
 (A) 3 MPa (C) 10 MPa
 (B) 6 MPa (D) 20 MPa
[Ans. C]
34. U_1 and U_2 are the strain energies stored in a prismatic bar due to axial tensile forces P_1 and P_2 , respectively. The strain energy U stored in the same bar due to combined action of P_1 and P_2 will be
 (A) $U = U_1 + U_2$ (C) $U < U_1 + U_2$
 (B) $U = U_1 U_2$ (D) $U > U_1 + U_2$
[Ans. D]

35. The right triangular truss is made of members having equal sectional area of 1550 mm^2 and Young's modulus of $2 \times 10^5 \text{ MPa}$. The horizontal deflection of the joint Q is



- (A) 2.47 mm (C) 14.31 mm
(B) 10.25 mm (D) 15.68 mm
[Ans. D]

36. The influence line diagram (ILD) shown is for the member



- (A) PS (C) PQ
(B) RS (D) QS
[Ans. A]

37. Consider the following statements

1. The compressive strength of concrete decreases with increase in water cement ratio of concrete mix
2. Water is added to concrete mix for hydration of cement and workability
3. Creep and shrinkage of concrete are independent of the water cement ratio in concrete mix.


The TRUE statements are

- (A) 1 and 2 (C) 2 and 3
(B) 1, 2 and 3 (D) 2 only
[Ans. B]

38. The percentage loss of pre-stress due to anchorage slip of 3 mm in a concrete beam of length 30m, which is post tensioned by a tendon with an initial stress of 1200 N/mm^2 and modulus of elasticity equal to $2.1 \times 10^5 \text{ N/mm}^2$ is

- (A) 0.0175 (C) 1.75
(B) 0.175 (D) 17.5
[Ans. C]


42. A bracket connection is made with four bolts of 10 mm diameter and supports a load of 10 kN at an eccentricity of 100 mm. The maximum force to be resisted by any bolt will be.



- (A) 5 kN (C) 6.8 kN
(B) 6.5 kN (D) 7.16 kN

[Ans. D]

43. The plastic collapse load W_p for the propped cantilever supporting two point loads as shown in figure in terms of plastic moment capacity, M_p is given by



- (A) $\frac{3M_p}{L}$ (C) $\frac{5M_p}{L}$
(B) $\frac{4M_p}{L}$ (D) $\frac{6M_p}{L}$

[Ans. B]

44. Sieve analysis on a dry soil sample of mass 1000 g showed that 980 g and 270 g of soil pass through 4.75 mm and 0.075 mm sieve, respectively. The liquid limit and plastic limits of the soil fraction passing through 425 μ sieves are 40% and 18%, respectively. The soil may be classified as

- (A) SC (C) CI
(B) MI (D) SM


[Ans. A]

45. The water content of a saturated soil and the specific gravity of soil solids were found to be 30% and 2.70, respectively. Assuming the unit weight of water to be 10 kN/m^3 , the saturated unit weight (kN/m^3) and the void ratio of the soil are

- (A) 19.4, 0.81 (C) 19.4, 0.45
(B) 18.5, 0.30 (D) 18.5, 0.45

[Ans. A]

46. The factor safety of an infinite soil slope shown in the figure having the properties $c = 0$, $\phi = 35^\circ$, $\gamma_{\text{dry}} = 16 \text{ kN/m}^3$, and $\gamma_{\text{sat}} = 20 \text{ kN/m}^3$ is approximately equal to



- (A) 0.7
(B) 0.8
(C) 1.0
(D) 1.2
[Ans. A]

47. Match List-I with List-II and select the correct answer using the codes given below the lists:

List -I

- A. Constant head permeability test
B. Consolidation test
C. Pycnometer test
D. Negative skin friction

List -II

1. Pile Foundation
2. Specific gravity
3. Clay soil
4. Sand

Codes:

- | | A | B | C | D |
|-----|---|---|---|---|
| (A) | 4 | 3 | 2 | 1 |
| (B) | 4 | 2 | 3 | 1 |
| (C) | 3 | 4 | 2 | 1 |
| (D) | 4 | 1 | 2 | 3 |


[Ans. A]

48. The bearing capacity of a rectangular footing of plan dimensions $1.5 \text{ m} \times 3 \text{ m}$ resting on the surface of a sand deposit was estimated as 600 kN/m^2 when the water table is far below the base of the footing. The bearing capacities in kN/m^2 when the water level rises to depth of 3 m, 1.5 m and 0.5 m below the base of the footing are

- (A) 600, 600, 400
(B) 600, 450, 350
(C) 600, 500, 250
(D) 600, 400, 250

[Ans. A]

49. What is the ultimate capacity in kN of the pile group shown in the figure assuming the group to fail as a single block?



- (A) 921.6
(B) 1177.6
(C) 2438.6
(D) 3481.6

[Ans. D]

50. A horizontal water jet with a velocity of 10 m/s and cross sectional area of 10 mm² strikes a flat plate held normal to the flow direction. The density of water is 1000 kg/m³. The total force on the plate due to the jet is

- (A) 100 N
(B) 10 N
(C) 1 N
(D) 0.1 N

[Ans. C]

51. A 1:50 scale model of a spillway is to be tested in the laboratory. The discharge in the prototype is 1000 m³/s. The discharge to be maintained in the model test is

- (A) 0.057 m³/s
(B) 0.08 m³/s
(C) 0.57 m³/s
(D) 5.7 m³/s

[Ans. A]

52. A triangular open channel has a vertex angle of 90° and carries flow at a critical depth of 0.30 m. The discharge in the channel is

- (A) 0.08 m³/s
(B) 0.11 m³/s
(C) 0.15 m³/s
(D) 0.2 m³/s

[Ans. B]

53. Flow rate of a fluid (density = 1000 kg/m³) in a small diameter tube is 800 mm³/s. The length and the diameter of the tube are 2 m and 0.5 mm, respectively. The pressure drop in 2 m length is equal to 2.0 MPa. The viscosity of the fluid is

- (A) 0.025 N-s/m²
(B) 0.012 N-s/m²
(C) 0.00192 N-s/m²
(D) 0.00102 N-s/m²

[Ans. C]

54. The flow rate in a wide rectangular open channel is 2.0 m³/s per meter width. The channel bed slope is 0.002. The Manning's roughness coefficient is 0.012. The slope of the channel is classified

- (A) Critical
(B) Horizontal
(C) Mild
(D) Steep

[Ans. D]

55. The culturable command area for a distributed channel is 20,000 hectares. Wheat is grown in the entire area and the intensity of irrigation is 50%. The kor period for wheat is 30 days and the kor water depth is 120 mm. The outlet discharge for the distributary should be
- (A) 2.85 m³/s (C) 4.63 m³/s
(B) 3.21 m³/s (D) 5.23 m³/s

[Ans. C]

56. An isolated 4-hour storm occurred over a catchment as follows:

Time	1 st hr	2 nd hr	3 rd hr	4 th hr
Rainfall (mm)	9	28	12	7

The ϕ index for the catchment is 10 mm/h. The estimated runoff depth from the catchment due to the above storm is

- (A) 10 mm (C) 20 mm
(B) 16 mm (D) 23 mm

[Ans. C]

57. Two electrostatic precipitators (ESPs) are in series. The fractional efficiencies of the upstream and downstream ESPs for size d_p are 80% and 65%, respectively. What is the overall efficiency of the system for the same d_p ?

- (A) 100% (C) 80%
(B) 93% (D) 65%

[Ans. B]

58. 50 g of CO₂ and 25 g of CH₄ are produced from the decomposition of municipal solid waste (MSW) with a formula weight of 120 g.

What is the average per capita greenhouse gas production in a city of 1 million people with a MSW production rate of 500 ton/day?

- (A) 104 g/day (C) 208 g/day
(B) 120 g/day (D) 313 g/day

[Ans. D]

59. The extra widening required for a two-lane national highway at a horizontal curve of 300 m radius, considering a wheel base of 8m and a design speed of 100kmph is

- (A) 0.42 m (C) 0.82 m
(B) 0.62 m (D) 0.92 m

[Ans. C]

60. While designing a hill road with a ruling gradient of 6%, if a sharp horizontal curve of 50 m radius is encountered, the compensated gradient at the curve as per the Indian roads congress specifications should be.

- (A) 4.4% (C) 5.0%
(B) 4.75% (D) 5.25%

[Ans. A]

61. The design speed on a road is 60 kmph. Assuming the driver reaction time of 2.5 seconds and coefficient of friction of pavement surface as 0.35, the required stopped distance for two-way traffic on a single lane road is.

(A) 82.1 m (C) 164.2 m
(B) 102.4 m (D) 186.4 m

[Ans. C]

62. The width of the expansion joint is 20 mm in a cement concrete pavement. The laying temperature is 20°C and the maximum slab temperature in summer is 60°C. The coefficient of thermal expansion of concrete is 10×10^{-6} mm/mm/°C and the joint filter compresses up to 50% of the thickness. The spacing between expansion joints should be

(A) 20 m (C) 30 m
(B) 25 m (D) 40 m

[Ans. B]

63. The following data pertains to the number of commercial vehicles per day for the design of a flexible pavement for a national highway as per IRC: 37-1984

Type of commercial vehicle	No. of vehicle per day considering the number of lanes	Vehicle Damage Factor
Two axle trucks	2000	5
Tandem axle trucks	200	6

Assuming a traffic growth factor of 7.5% per annum for both the types of vehicles. The cumulative number of standard axle standard axle load repetitions (in million) for a design life ten years is

(A) 44.6 (C) 62.4
(B) 57.8 (D) 78.7

[Ans. B]

64. Match the following test on aggregate and its properties

Test	Property
P. Crushing test	1. Hardness
Q. Los Angles abrasion test	2. Weathering
R. Soundness test	3. Shape
S. Angularity test	4. Strength

(A) P-2, Q-1, R-4, S-3 (C) P-3, Q-2, R-1, S-4
(B) P-4, Q-2, R-3, S-1 (D) P-4, Q-1, R-2, S-3

[Ans. D]

65. The plan of map was photo-copied to a reduced size such that a line originally 100 mm was measured 90 mm. The original scale of the plan was 1:1000. The revised scale is

(A) 1:900 (C) 1:1121
(B) 1:1111 (D) 1:1221

[Ans. B]

66. The following table gives data of consecutive coordinates in respect of a closed theodolite traverse PQRSP.

Station	P	Q	R	S
Northing, m	400.75	100.25		
Southing, m			199.0	300.0
Easting, m		199.25	399.75	
Westing, m	300.5			200.5

The magnitude and direction of error of closure in whole circle bearing are.

- (A) 2.0m and 45° (C) 2.82m and 315°
(B) 2.0m and 315° (D) 3.42m and 45°

[Ans. C]

67. The following measurements were made during testing a leveling instrument.

Instrument at	Staff reading At	
	P ₁	Q ₁
P	2.800 m	1.700 m
Q	2.700 m	1.800 m

P₁ is close to P and Q₁ is close to Q. If the reduced level of station P is 100.000 m, the reduced level of station Q is

- (A) 99.000 m (C) 101.000 m
(B) 100.000 m (D) 102.000 m

[Ans. C]

68. Two straight line intersect at an angle of 60° . The radius of a curve joining the two straight lines is 600 m. The length of long chord and mid-ordinates in meters of the curve are

- (A) 80.4, 600.0 (C) 600.0, 39.89
(B) 600.0, 80.4 (D) 49.89, 300.0

[Ans. B]


69. The magnetic bearing of a line AB is $S 45^\circ E$ and the declination is 5° west. The true bearing of the line AB is

- (A) $S 45^\circ E$ (B) $S 40^\circ E$ (C) $S 50^\circ E$ (D) $S 50^\circ W$

[Ans. C]

Common Data for Question 70 and 71

Water is flowing through the permeability apparatus as shown in the figure. The coefficient of permeability of the soil is 'k' m/s and the porosity of the soil sample is 0.50



70. The total head, elevation head and pressure head in metres of water at the point R shown in the figure are
 (A) 0.8,0.4,0.4 (C) 0.4,0,0.4
 (B) 1.2,0.4,0.8 (D) 1.6,0.4, 1.2

[Ans. A or C]

71. What are the discharge velocity and seepage velocity through the soil sample?

- (E) $k, 2k$ (C) $2k, k$
 (B) $\frac{2}{3}k, \frac{4}{3}k$ (D) $\frac{4}{3}k, \frac{2}{3}k$

[Ans. A]

Common Data Questions 72 and 73

Ordinates of a 1 - hour unit hydrograph at 1 hour intervals, starting from time $t = 0$, are 0, 2, 6, 4, 2, 1 and $0 \text{ m}^3/\text{s}$.

72. Catchment area represented by this unit hydrograph is
 (A) 1.0 km^2 (C) 3.2 km^2
 (B) 2.0 km^2 (D) 5.4 km^2

[Ans. D]

73. Ordinate of a 3 - hour unit hydrograph for the catchment at $t = 3$ hour is

- (A) $2.0 \text{ m}^3/\text{s}$ (C) $4.0 \text{ m}^3/\text{s}$
 (B) $3.0 \text{ m}^3/\text{s}$ (D) $5.0 \text{ m}^3/\text{s}$

[Ans. C]

Common Data for Questions 74 and 75

A completely mixed activated sludge process is used to treat a wastewater flow of 1 million litres per day (1 MLD) having a BOD_5 of 200 mg/L. The biomass concentration in the aeration tank is 2000 mg/L and the concentration of the net biomass leaving the system is 50 mg/L. the aeration tank has a volume of 200 m^3

74. What is the hydraulic retention time of the wastewater in aeration tank?

- (A) 0.2h (C) 10h
 (B) 4.8h (D) 24h

[Ans. B]

75. What is the average time for which the biomass stays in the system?

- (A) 5h (C) 2 days
 (B) 8h (D) 8 days

[Ans. D]

Linked Answer Question 76 and 77

A two span continuous beam having equal spans each of length L is subjected to a uniformly distributed load w per unit length. The beam has constant flexural rigidity.

76. The reaction at the middle support is

- (A) wL (C) $\frac{5wL}{4}$
 (B) $\frac{5wL}{2}$ (D) $\frac{5wL}{8}$

[Ans. C]

77. The bending moment at the middle support is
- (A) $\frac{wL^2}{4}$ (C) $\frac{wL^2}{12}$
 (B) $\frac{wL^2}{8}$ (D) $\frac{wL^2}{16}$
- [Ans. B]**

Statement for Linked Answer Question 78 and 79

A single reinforced rectangular concrete beam has a width of 150mm and an effective depth of 330mm. The characteristic compressive strength of concrete is 20 MPa and the characteristic tensile strength of steel is 415 MPa. Adopt the stress block for concrete as given in IS:456-2000 and take limiting value of depth of neutral axis as a 0.48 times the effective depth of the beam.


78. The limiting value of the moment of resistance of the beam in kN-m is
- (A) 0.14 (C) 45.08
 (B) 0.45 (D) 156.82
- [Ans. C]**

79. The limiting area of tension steel in mm² is
- (A) 473.9 (C) 373.9
 (B) 412.3 (D) 312.3
- [Ans. A]**

Statement for Linked Answer Question 80 and 81

The ground conditions at a site are as shown in the figure. The water table at the site which was initially at a depth of 5 m below the ground level got permanently lowered to a depth of 15 m below the ground level due to pumping of water over a few years. Assume the following data:

- (i) Unit weight of water = 10 kN/m³
- (ii) Unit weight of sand above water table = 18 kN/m³
- (iii) Unit weight of sand and clay below the water table = 20 kN/m³
- (iv) Coefficient of volume compressibility = 0.25 m²/MN



80. What is the change in the effective stress in kN/m² at mid-depth of the clay layer due to the lowering of the water table?
- (A) 0 (C) 80
 (B) 20 (D) 100
- [Ans. D]**

81. What is the compression of the clay layer in mm due to the lowering of the water table?
 (A) 125 (C) 25
 (B) 100 (D) 0

[Ans. A]

Statement for Linked Answer Question 82 and 83

A rectangular open channel needs to be designed to carry a flow of $2.0 \text{ m}^3/\text{s}$ under uniform flow conditions. The Manning's roughness coefficient is 0.018. The channel should be such that the flow depth is equal to half width and the Froude number is equal to 0.5

82. The bed slope of the channel to be provided is
 (A) 0.0012 (C) 0.0025
 (B) 0.0021 (D) 0.0052

[Ans. B]

83. Keeping the width, flow depth and roughness the same. If the bed slope of the above channel is doubled. The average boundary shear stress under uniform flow conditions is
 (A) 5.6 N/m^2 (C) 12.3 N/m^2
 (B) 10.8 N/m^2 (D) 17.2 N/m^2

[Ans. D]

Statement for Linked Answer Question 84 and 85

A plain sedimentation tank with a length of 20m, width of 10m and a depth of 3m is used in a water treatment plant to treat 4 million litres of water per day (4 MLD). The average temperature of water is 20°C . The dynamic viscosity of water is $1.002 \times 10^{-3} \text{ N.s/m}^2$ at 20°C . Density of water is 998.2 kg/m^3 . Average specific gravity of particle is 2.65

84. What is the surface overflow rate in the sedimentation tank?
 (A) $20 \text{ m}^3/\text{m}^2/\text{day}$ (C) $67 \text{ m}^3/\text{m}^2/\text{day}$
 (B) $40 \text{ m}^3/\text{m}^2/\text{day}$ (D) $133 \text{ m}^3/\text{m}^2/\text{day}$

[Ans. A]

85. What is the minimum diameter of the particle which can be removed with 100% efficiency in the above sedimentation tank?
 (A) $11.8 \times 10^{-3} \text{ mm}$ (C) $50 \times 10^{-3} \text{ mm}$
 (B) $16.0 \times 10^{-3} \text{ mm}$ (D) $160 \times 10^{-3} \text{ mm}$

[Ans. B]